

GRAP EP1 & EP2

EXTREME PRESSURE GREASES

GRAP EP1 & EP2 are premium quality lithium base greases having extreme pressure(EP) properties. These greases prevent welding and seizure of moving parts often caused by shock loading and water washout.

PERFORMANCE STANDARDS: BIS 7623-1993 (Second Revision)

IPSS 1-09-005

CHARACTERISTICS	GRAP	
	EP1	EP2
Colour	Dark brown	Dark brown
Structure	Smooth	Smooth
Soap type	Lithium	Lithium
Base oil viscosity @40°C cSt, min	90	90
Penetration @25°C, 60 strokes	310-340	265-295
Drop point, °C, min	180	180
Rust test ASTM D-1743	Pass	Pass
Timken OK load, lbs, min ASTM 2509	40	40

APPLICATIONS:

Recommended for both plain and anti-friction bearings in a wide variety of applications such as automotive, earth moving equipments, gear couplings, electric motors, mining equipments and general industrial machinery.

PERFORMANCE BENEFITS:

- Excellent shear stability
- High load carrying capacity
- High oxidation stability
- Good anti-rust & anti-corrosion properties

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.