

RPAP A SUPER

(AROMATIC RUBBER PROCESS OIL)

RPAP A SUPER is aromatic type rubber processing oil confirming to ASTM 101 Type, formulated from specially selected aromatic extracts.

It has good compatibility and suitable for use in NR, SBR, PBR, NBR, CR.

Sr No	Characteristics	Unit	Test Method	Guaranteed Data		
				Min	Max	
1	Color		ASTM D-1500	Dark Brownish Black (>8)		
2	Density at 29.5°C	gm/ml	ASTM D-1298	1.0 Typical		
3	Kinematic Viscosity at 100°C	cSt	ASTM D-445	18	28	
4	Flash Point, COC	°C	ASTM D-92	220		
5	Pour Point	°C	ASTM D-97		+30	
6	Aniline Point	°C	ASTM D-611	25	50	
7	Viscosity Gravity Constant		ASTM D-2501	0.93	0.98	
8	Neutralization Number	mg KOH/gm	ASTM D-974		1.0	
9	Clay Gel Analysis	Asphaltenes	%	ASTM D-2007	Nil	
		Aromatics			75 (Typical)	
		Polar Compounds			13 (Typical)	
		Saturates			12 (Typical)	

APPLICATIONS: RPAP A SUPER is suitable for the following applications:

- Manufacturing of Automotive Tyre & Tube
- Tyre retreading
- Belting & Hoses
- Battery Containers
- All NR extruded products

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.