

SFCPC-Toluene (Industrial Grade)

© Application: A solvent for various kinds of resins, such as polyalcoholic acid, Melamine, phenolic formaldehyde, urea and formaldehyde; a solvent for shellac, paints, enamel, varnish and adhesives; and a thinner and diluent.

Item	Specification	Test Method	
		CNS	ASTM
Appearance	Clear liquid free of haze or sediment at 18.3~25.6°C	Visual	Visual
Sp. Gr. at 15°C/15°C	0.864~0.874	14474	D4052
Density, 20°C, g/ml	0.861~0.871	14474	D4052
Color, Pt-Co Scale	max. 20	2755 K6254	D1209
Distillation Range, °C (at 760 mm Hg)	2 max, including 110.6°C	2756 K6255	D850
Nonaromatics, vol%	max. 1.5	2761 K6260	D2360
Acidity	Nil	2758 K6257	D847
Acid Wash Color	max No. 4	2757 K6256	D848
Copper Corrosion (1/2 hr. At 100°C)	Color changed, no more than 2 nd level in D1616	2760 K6259	D849
Water	No haze at 20°C	1474 K1066	Visual
Hydrogen Sulfide and Sulfur Dioxide (H ₂ S, SO ₂)	Nil	2759 K6258	D853

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.