

PRODUCT DATA SHEET

SFCPC-Toluene (Nitration Grade)

© Application: A solvent for various kinds of resins, such as polyalcoholic acid, Melamine, phenolic formaldehyde, urea and formaldehyde; a solvent for shellac, paints, enamel, varnish and adhesives; a thinner and diluents; and feedstock of T.N.T. and petrochemicals.

* Specification:

Item	Specification	ASTM Test Method
Appearance	Clear liquid free of haze or sediment at 18.3~25.6°C	Visual
Sp. Gr. (at 15°C/15°C)	0.869~0.873	D3505
Density(20°C, g/ml)	0.865~0.870	D3505
Color, Pt-Co Scale, max.	20	D1209
Distillation Range (°C, at 760 mm Hg)	max.1, including 110.6°C	D850
Nonaromatics, vol, max.	1.5	D2360
Acidity	Nil	D847
Acid Wash Color, max.	No.2	D848
Corrosion, Copper	No copper iridescence; free of gray or black sediment; no signs of tarnish	D849
Hydrogen Sulfide and Sulfur Dioxide (H ₂ S, SO ₂)	Nil	D853

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.