



騰華能源實業有限公司 TENOIT CO. Ltd.

台北市內湖區民權東路六段 109 號 5 樓之 4 網址: <http://www.tenoit.com.tw>

Tel : 886-2-8792-2185 Fax : 886-2-8792-2151

Product Data Sheet

SFEXX-ISO-M(AM) (Isoparaffin Fluid)

Clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulphur.

Properties		Typical Value (English)	Typical Value (SI)	Test Based On
1	Distillation Range Initial Boiling Point (IBP) Dry Point (DP)	437°F 487°F	225°C 253°C	ASTM D86
2	Flash Point (Method A)	201°F	94°C	ASTM D93
3	Aromatic Content (UV)	40 wtpm	40 wtpm	
4	Density (60.0°F(15.6°C))	6.55 lb/gal	0.785 g/ml	ASTM D4052
5	Vapor Pressure (68.0°F(20.0°C))	<0.1 mm Hg	<0.01 kPa	
6	Aniline Point (Method E)	199°F	93°C	ASTM D611
7	Kinematic Viscosity (77°F(25°C))	4.23 cSt	4.23 mm ² /s	ASTM D445

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.