



騰華能源實業有限公司 TENOIT CO. Ltd.

台北市內湖區民權東路六段 109 號 5 樓之 4 網址: <http://www.tenoit.com.tw>

Tel : 886-2-8792-2185 Fax : 886-2-8792-2151

Product Data Sheet

SFSK-ISOL-C

	CHARACTERISTICS	TYPICAL VALUE	SPECIFICATIONS	TEST METHOD
1	Color, Saybolt	-	Min +30	ASTM D156
2	Specific Gravity (15.56/15.56°C)	-	0.692-0.702	ASTM D 4052
3	Distillation at 760mmHg Initial Boiling Point °C Dry point °C	-	Min 94 Max 108	ASTM D86
4	Flash Point- TCC °C	-	Min 10	ASTM D56
5	Aniline Point °C	-	76-84	ASTM D611
6	Total Sulfur wt ppm	-	Max 1	ASTM D3961
7	Aromatics vol ppm	-	Max 200	UV
8	Bromine Index (D 1492) mg/100g	-	Max 5	ASTM D1492
9	2,2,4 Trimethyl-Pentane wt%	-	Min 80	G. C

1. Typical values, where stated, are to be considered as representative of current production and should not be treated as specifications.

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.