



騰華能源實業有限公司 TENOIT CO. Ltd.

台北市內湖區民權東路六段 109 號 5 樓之 4 網址: <http://www.tenoit.com.tw>

Tel : 886-2-8792-2185 Fax : 886-2-8792-2151

Product Data Sheet

SFSK-ISOL-G

	CHARACTERISTICS	TYPICAL VALUE	SPECIFICATIONS	TEST METHOD
1	Color, Saybolt	-	Min +30	ASTM D156
2	Specific Gravity (15.56/15.56°C)	-	0.730-0.755	ASTM D 4052
3	Distillation at 760mmHg Initial Boiling Point °C Dry point °C	-	Min 153 Max 179	ASTM D86
4	Flash Point- TCC °C	-	Min 38	ASTM D56
5	Aniline Point °C	-	77-85	ASTM D611
6	Total Sulfur wt ppm	-	Max 5	ASTM D3961
7	Aromatics vol ppm	-	Max 100	UV
8	Bromine Index (D 1492) mg/100g	-	Max 20	ASTM D1492
9	Kinematics Viscosity 40°C mm ² /sec	-	1.000-1.350	ASTM D445

1. Typical values, where stated, are to be considered as representative of current production and should not be treated as specifications.

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.