



SFSS-CD-100

De-Aroma Solvent

Test Item	Unit	Specification	Test Results	Test Method
Appearance	-	Clear	Clear	Visual
Specific Gravity, at 15°C	g/cm ³	0.830 ± 0.02	0.8308	ASTM D 4052
Distillation IBP		Min 235	245.2	ASTM D 86
5%		-	258.7	
10%		-	259.1	
50%	°C	-	260.9	
90%		-	265.7	
95%		-	267.7	
FBP		Max 275	273.4	
Flash Point (P-M)	°C	Min 100	120	ASTM D 93
Aniline Point	°C	Min 70	78.2	ASTM D 611
Sulfur Content	mg/kg	Max 3	0.00	ASTM D 5453
Saybolt Color	-	Min +30	+30	ASTM D 156
Refractive Index (N _D 20)	-	-	1.4546	ASTM D 1218
Brome Index (BI)	mgBr ₂ /100g	-	0	ASTM D 2710
Water Content	μg/g	-	39	ASTM D 1744
Corrosion Copper Strip (3hr/50°C)	-	Max 1	1a	ASTM D 130
Kinematic Viscosity	mm ² /s, 40°C	Min 2.5	2.857	ASTM D 445
Aromatic Content	Wt%	Max 0.5	0.02	UOP495

- Environment-friendly, high-boiling point solvent with excellent response stability and being harmless to human body.
- Aerosol, Ink, Metal working oil, Rolling oil, PVC viscosity modifiers, Polymer cohesion agent, Etc.

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.