



SFSS-CD-160

De-Aroma Solvent

Test Item	Unit	Specification	Test Results	Test Method
Appearance	-	Clear	Clear	Visual
Specific Gravity, at 15°C	g/cm ³	-	0.8371	ASTM D 4052
Distillation IBP	°C	Min 300	311.3	ASTM D 86
5%		-	321.4	
10%		-	323.2	
50%		-	329.2	
90%		-	348.9	
95%		-	357.5	
FBP		Max 380	361.5	
Flash Point (P-M)	°C	Min 150	167	ASTM D 93
Aniline Point	°C	Min 95	98.2	ASTM D 611
Sulfur Content	mg/kg	Max 3	0.00	ASTM D 5453
Saybolt Color	-	Min +26	27	ASTM D 156
Refractive Index (N _D 20)	-	-	1.4598	ASTM D 1218
Brome Index (BI)	mgBr ₂ /100g	-	0	ASTM D 2710
Water Content	μg/g	-	17	ASTM D 1744
Corrosion Copper Strip (3hr/50°C)	-	Max 1	1a	ASTM D 130
Kinematic Viscosity	mm ² /s, 40°C	-	7.650	ASTM D 445
Aromatic Content	Wt%	Max 0.5	0.06	UOP495

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.