



SFSS-CD-40

De-Aroma Solvent

Test Item	Unit	Specification	Test Results	Test Method
Appearance	-	Clear	Clear	Visual
Specific Gravity, at 15°C	g/cm ³	0.780 ± 0.02	0.796	ASTM D 4052
Distillation IBP		Min 155	158.2	ASTM D 86
5%		-	163.3	
10%		-	164.3	
50%	°C	-	171.0	
90%		-	183.5	
95%		-	186.6	
FBP		Max 200	196.2	
Flash Point (P-M)	°C	Min 38	51	ASTM D 93
Aniline Point	°C	Min 45	61.2	ASTM D 611
Sulfur Content	mg/kg	Max 1	0.06	ASTM D 5453
Saybolt Color	-	Min +30	+30	ASTM 1500
Refractive Index (N _D 20)	-	-	1.4354	ASTM D 1218
Brome Index (BI)	mgBr ₂ /100g	50 ↓	0	ASTM D 2710
Water Content	μg/g	-	39	ASTM D 1744
Copper Corrosion	-	Max 1	1a	ASTM D 130
Kinematic Viscosity	mm ² /s, 40°C	-	1.038	ASTM D 445
	mm ² /s, 100°C	-	-	
Aromatic Content	Wt%	Max 0.1	0.09	UOP495

- Aromatic substance-eliminated, environment-friendly, and odorless solvent with a high solubility.
- Paint, Ink, Cleaning agent, Wax solvent, Dry cleaning, Construction putty, Etc.

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.