



SFSS-CD-80

De-Aroma Solvent

Test Item	Unit	Specification	Test Results	Test Method
Appearance	-	Clear	Clear	Visual
Specific Gravity, at 15°C	g/cm ³	0.820 ± 0.02	0.8231	ASTM D 4052
Distillation IBP		Min 205	207.5	ASTM D 86
5%		-	210.5	
10%		-	213.4	
50%	°C	-	219.5	
90%		-	229.0	
95%		-	235.8	
FBP		Max 245	237.7	
Flash Point (P-M)	°C	Min 65	83	ASTM D 93
Aniline Point	°C	Min 60	69.6	ASTM D 611
Sulfur Content	mg/kg	Max 3	0.00	ASTM D 5453
Saybolt Color	-	Min +30	+30	ASTM D 156
Refractive Index (N _D 20)	-	-	1.4496	ASTM D 1218
Brome Index (BI)	mgBr ₂ /100g	-	0	ASTM D 2710
Water Content	μg/g	-	41	ASTM D 1744
Corrosion Copper Strip (3hr/50°C)	-	Max 1	1a	ASTM D 130
Kinematic Viscosity	mm ² /s, 40°C	Min 1.5	1.752	ASTM D 445
Aromatic Content	Wt%	Max 0.5	0.01	UOP495

- Products with a high solubility, response stability, oxidative stability.
- Cleaning agent, Electric discharge machining oil, Sealant Metal working oil, Anti-rust oil, Etc.

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.