

Material Safety Data Sheet

Section 1 - Chemical Product and Company Identification

Product Name : TRANSFORMER OIL TOAP 1020-60H

Chemical Family : Petroleum Distillate.

Chemical Formula : Not Applicable

CAS Number : 64742-55-8

Company Details : TENOIT CO., LTD.

Room 4, 5FL., No. 109, Sec. 6, Mingquan East Road, Taipei, Taiwan

EMERGENCY TELEPHONE NUMBER : TEL (886) 2 8792-2185 8792-2187

FAX (886) 2 8792-2151

Section 2 - Composition And Information On Hazardous Ingredients

Ingredient	CAS Number	Percentage	Hazardous
Severely Hydrotreated Light Paraffinic Petroleum Oil.	64742-55-8	100	No

Section 3 - Hazardous Identification

Potential Health Effects

Primary Entry Route : Skin

Inhalation : Inhalation of vapors or mist may be irritating to respiratory passages. Prolonged exposure may result in dizziness and nausea. Target Organ for mineral oil mist is lungs.

Eye : Eye contact may result in slight irritation and redness.

Skin : Short term contact with skin is unlikely to cause any problems ; excessive or prolonged and repeated contact and poor hygiene conditions may result in dryness, dermatitis, oil acne, cracking and defatting of the skin. Personnel with pre-existing skin disorders should avoid contact with this product.

Ingestion : May result in nausea or stomach discomfort.

Section 4 - First Aid Measures

Eye Contact : Flush eyes immediately with plenty of water 15 minutes or until irritation. If redness persists, seek medical help.

Skin Contact : Wash thoroughly with soap and water. Remove contaminated clothing. Reuse only after clearing.

Inhalation : Remove to fresh air. Assist breathing if necessary. Seek medical help.

Aspiration : If there is any suspicion of aspiration into the lungs obtain medical advice.

Ingestion : If swallowed, observe for signs of stomach discomfort or nausea. If symptoms persist, seek medical help. Do not induce vomiting.

Section 5 - Fire Fighting Measures

Flash Point : >140°C , **Flash Point Method :** COC

Auto ignition Temperature : >315°C

Lower Explosive Level(LEL):Not determined.

Upper Explosive Limit(UEL) : Not determined.

Flammability Classification : OSHA CLASS III-B Combustible Liquid.

Extinguishing Media : Dry Chemical Powder, Foam, CO₂ and water or fog. Water may be used to cool below flash point.

Unusual Fire or Explosion Hazards : Do not use forced stream as this could cause fire to spread.

Combustion Products : Fumes, Smoke, and Carbon monoxide.

Fire-fighting Instruction and Equipment : Use water to cool containers exposed to flames.

Do not enter enclosed or a confined work space without proper protective equipment.

Fire fighting personnel should wear respiratory protection (positive pressure if available).

Material Safety Data Sheet

Section 6 - Accidental release Measures

Spill/Leak Procedures: Stop spill at source if possible without risk. Contain spill. Eliminate sources of ignition Spill area will be slick. Recover all possible material for reclamation. Use non-flammable absorbent material to pick up remainder of spill.
Spill to navigable Waters: If this material is spilled into navigable waters and creates a visible sheen, it is reportable to Local Response Centre.

Section 7 - Handling and Storage

Handling and storage Precautions : Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty oil containers can contain explosive vapors. NFPA Class IIIB storage. Wash thoroughly after handling.
Work/Hygienic Practices : Wash hands with soap and water before eating, drinking, smoking or use of toilet facilities. Take shower after work if general contact occurs. Remove oil-soaked and launder before reuse. Discard contaminated shoes and leather gloves.

Section 8 - Exposure Controls/Personal Protection

Engineering Controls : Adequate ventilation is required where excessive heating or agitation may occur to maintain concentration below exposures limits.
Eye/Face Protection : Safety glasses or face shield where splashing is possible.
Skin Protection : Avoid prolonged and or repeated skin contact. If prolonged contact cannot be avoided, wear protective gloves (solvent resistant gloves) and clothing.
Respiratory Protection : Normally not required. Respirator should be used in areas where vapor concentration is excessive due to high temperatures or where oil misting occurs.

Section 9 - Physical and Chemical Properties

Appearance : Clear, pale straw to yellow, Heavy liquid	Vapor Pressure(mm Hg) : 0.0059 mm Hg at 100°F
Odor : Mild petroleum odor.	Evaporation Rate : Not applicable.
Specific Gravity : 0.81 to 0.89 (Water = 1)	Solubility(H₂O) : Negligible.
% Volatiles by volume @21°C(70°F) : Nil	PH : Not applicable.
Melting Point : Not applicable	Boiling Point : > 271°C
	Vapor Density(Air=1) : > 5

Section 10 - Stability and reactivity

Stability : Stable under ordinary conditions of use and storage.
Polymerization : Polymerization will not occur.
Chemical Incompatibilities : Strong oxidizers.
Condition to Avoid : Source of ignition.
Hazardous Decomposition Products : Combustion may produce carbon monoxide and carbon dioxide.

Section 11 - Toxicological Information

Eye Effects : Minimal irritation on contact.
Skin Effects : Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.
Acute Oral Effects : Tests on similar material indicate low order of acute oral toxicity.
Acute Inhalation Effects : Low acute toxicity expected on inhalation.

Section 12 - Ecological Information

Environmental Fate : No information found.
Environmental Toxicity: No information found.

