Section 1 - Chemical Product and Company Identification				
Product Name : TRANSFORMER OI	L TOAP 1020-60UT			
Chemical Family: Petroleum Distillate.				
Chemical Formula: Not Applicable				
CAS Number : 64742-53-6				
Company Details : TENOIT CO.,	LTD.			
		quan East Road, Taipei	. Taiwan	
EMERGENCY TELEPHONE NUMBER :			, 101.001	
	FAX (886) 2 8792			
Section 2 - Composition And Information On Hazardous Ingredients				
Ingredient	CAS Number	Percentage	Hazardous	
Severely Hydrotreated Light	64742-53-6	99.92	No	
Naphthenic Petroleum 0il.	04142 55 0	55.52	NO	
Inhibitor	128-37-0	0.08	No	
	128-37-0	0.08	No	
Section 3 - Hazardous Identification				
Potential Health Effects				
Primary Entry Route : Skin		, , ,		
Inhalation : Inhalation of v				
	ay result in dizz	ziness and nausea. Targ	get Organ for mineral	
oil mist is lungs.				
Eye: Eye contact may result in slight irritation and redness.				
Skin: Short term contact with skin is unlikely to cause any problems; excessive or prolonged				
and repeated contact an	d poor hygiene co	onditions may result in	dryness, dermatitis,	
oil acne, cracking and defatting of the skin. Personnel with pre-existing skin				
disorders should avoid	contact with the	is product.		
Ingestion: May result in nausea or stomach discomfort.				
Section 4 - First Aid Measures				
Eye Contact: Flush eyes immediately with plenty of water 15 minutes or until irritation.				
If redness persists, seek medical help.				
Skin Contact : Wash thoroughly with soap and water. Remove contaminated clothing. Reuse only after clearing.				
5		thing if necessary Se	ek medical heln	
Inhalation : Remove to fresh air. Assist breathing if necessary. Seek medical help. Aspiration : If there is any suspicion of aspiration into the lungs obtain medical advice.				
Ingestion : If swallowed, observe for signs of stomach discomfort or nausea. If symptoms				
persist, seek medical help. Do induce vomiting.				
Section 5 - Fire Fighting Measures				
Flash Point : >140°C , Flash Point Method : COC				
Auto ignition Temperature : >315°C				
Lower Explosive Level(LEL):Not determined.				
Upper Explosive Limit(UEL) : Not determined.				
Flammability Classification : OSHA CLASS III-B Combustible Liquid.				
Extinguishing Media : Dry Chemical Powder, Foam, CO ₂ and water or fog. Water may be used to				
cool below flash point.				
Unusual Fire or Explosion Hazards : Do not use forced stream as this could cause fire to				
Combustion Products · Fumas	spread.			
	Combustion Products : Fumes, Smoke, and Carbon monoxide. Fire-fighting Instruction and Equipment : Use waste to cool containers exposed to flames.			
Do not enter enclosed or a confined work space without proper protective equipment.				
Fire fighting personnel should wear respiratory protection (positive pressure if				
available).				

Section 6 - Acci	dental release Measures		
Spill/Leak Procedures: Stop spill at source if possible without risk. Contain spill.			
Eliminate sources of ignition Spill area will be slick. Recover all possible material for reclamation. Use non-flammable absorbent material to pick up remainder of spill.			
Spill to navigable Waters: If this material is spilled into navigable waters and creates			
a visible sheen, it is reportable to Local Response Centre.			
Section 7 - Handling and Storage			
Handling and storage Precautions : Keep away from flames, sparks or hot surfaces. Never use			
a torch to cut or weld on or near container. Empty oil containers can contain explosive			
vapors. NFPA Class IIIB storage. Wash thoroughly after handling.			
	soap and water before eating, drinking, smoking		
	nower after work if general contact occurs. Remove		
oil-soaked and launder before reuse. Discard contaminated shoes and leather gloves.			
Section 8 - Exposure Controls/Personal Protection			
Engineering Controls : Adequate ventilation is required where excessive heating or agitation			
may occur to maintain concentration below exposures limits.			
Eye/Face Protection: Safety glasses or face shield where splashing is possible.			
Skin Protection : Avoid prolonged and or repeated skin contact. If prolonged contact cannot			
be avoided, wear prot	ective gloves (solvent resistant gloves) and		
clothing.			
Respiratory Protection : Normally not required. Respirator should be used in areas where			
vapor concentrati	on is excessive due to high temperatures or where		
oil misting occurs.			
Section 9 - Physical and Chemical Properties			
Appearance : Clear, pale straw to yellow,	Vapor Pressure(mm Hg): 0.0059 mm Hg at 100°F		
Heavy liquid	Evaporation Rate : Not applicable.		
Odor: Mild petroleum odor.	Solubility(H ₂ O): Negligible.		
Specific Gravity: 0.81 to 0.89	PH: Not applicable.		
(Water = 1)	Boiling Point :> 271°C		
% Volatiles by volume @21°C(70°F) : Nil	Vapor Density(Air=1):> 5		
Melting Point: Not applicable			
Section 10 - Stability and reactivity			
Stability: Stable under ordinary conditions of use and storage.			
Polymerization : Polymerization will not occur.			
Chemical Incompatibilities: Strong oxidizers.			
Condition to Avoid: Source of ignition.			
Hazardous Decomposition Products : Combustion may produce carbon monoxide and carbon dioxide •			
Section 11 - Toxicological Information			
Eye Effects: Minimal irritation on contact.			
Skin Effects : Practically non-toxic if absorbed. May cause mild irritation with prolonged			
and repeated exposure.			
Acute Oral Effects: Tests on similar material indicate low order of acute oral toxicity.			
Acute Inhalation Effects: Low acute toxicity expected on inhalation.			
	cological Information		
Environmental Fate : No information found			
Environmental Toxicity, No information	Environmental Toxicity: No information found.		
Environmental loxicity: No information .	ound		

Section 13 - Disposal Considerations			
Follow National, State and Local regulations. Not a RCRA hazardous waste if uncontaminated.			
If "used", RCRA criteria must be determined. Do not flush to drain/storm sewer. If			
permitted incineration may be practical. Consider recycling.			
Section 14 - Transport Information			
DOT Shipping Label: Not regulated by DOT			
Section 15 - Regulatory Information			
CERCLA/SARA:			
302/303/304 categories : Extremely hazardous substances : None			
311/312 categories : Immediate(acute) Health Effects : No			
Delayed(chronic) health effects : No			
Fire Hazards : No			
313 categories : Toxic Chemicals(40 cFR 372) : None			
Clean Air act : Hazardous Air Pollutants(HAPS) : None			
Ozone depleting Compounds(ODC) : None			
OSHA(29CFR 1910) : This product is not hazardous under Hazard Communication Standard 29 CFR 1910.1200			
EPA/TSCA Inventory: The components of this product are listed on the EPA/TSCA inventory			
of chemicals CAS No: 64742-53-6			
Foreign Inventories : The components of this product are listed under the following			
inventories :			
1. CANADA DSL No.: 64742-53-6			
2. European Union's EINICS No. 265 - 156 – 6			
3. Korea's ECL No. KE – 12552			
4. Australia's ACS No. 64742 - 53 –6			
5. Philippine's PICCS - on list			
Section 16 - Other Information			
Hazard Rating NFPA/HMIS Classification			
0 = Least $1 = Slight$ $2 = Moderate$ Health = 1			
3 = High $4 = Extreme$ Fire = 1			
Reactivity = 0			

Disclaimer:

The information contained herein is based upon data believed to be reliable and reflects our best professional judgment. It is the responsibility of the user to determine the suitability of the material for their purpose. No warranty is expressed or implied, is given.