Section 1 - Chemical Product and Company Identification					
Product Name: TRANSFORMER OIL TOAP 1020BSX					
Chemical Family : Petroleum Distillate.					
Chemical Formula : Not Applic	-				
CAS Number: 64742-53-6					
Company Details : TENOIT CO.,	I TD				
		quan East Road, Taipei	Taiwan		
			, lalwall		
EMERGENCY TELEPHONE NUMBER :					
	FAX (886) 2 8792-2151 Section 2 - Composition And Information On Hazardous Ingredients				
Ingredient	CAS Number	Percentage	Hazardous		
Severely Hydrotreated	64742-53-6	99.6 to 99.92	No		
Naphthenic Petroleum Oil.					
Inhibitor	128-37-0	0.08 to 0.4	No		
Sectio	n 3 - Hazardo	ous Identification			
Potential Health Effects					
Primary Entry Route : Skin					
Inhalation : Inhalation of v	apors or mist ma	ay be irritating to r	espiratory passages.		
Prolonged exposure ma	ay result in dizz	ziness and nausea. Targ	get Organ for mineral		
oil mist is lungs.					
Eye : Eye contact may result	in slight irrita [.]	tion and redness.			
Skin: Short term contact with			excessive or prolonged		
and repeated contact an					
oil acne, cracking and					
			in pro entering entri		
disorders should avoid contact with this product. Ingestion: May result in nausea or stomach discomfort.					
Section 4 - First Aid Measures					
Eye Contact: Flush eyes immediately with plenty of water 15 minutes or until irritation.					
If redness persists, seek medical help.					
Skin Contact : Wash thoroughly with soap and water. Remove contaminated clothing. Reuse only					
after clearing.					
Inhalation : Remove to fresh air. Assist breathing if necessary. Seek medical help.					
Aspiration : If there is any suspicion of aspiration into the lungs obtain medical advice.					
Ingestion: If swallowed, observe for signs of stomach discomfort or nausea. If symptoms					
persist, seek medical help. Do induce vomiting.					
Section 5 - Fire Fighting Measures					
Flash Point : $>140^{\circ}$ C , Flash Point Method : COC					
Auto ignition Temperature : >315°C					
Lower Explosive Level(LEL):Not determined.					
Upper Explosive Limit(UEL): Not determined.					
Flammability Classification : OSHA CLASS III-B Combustible Liquid.					
Extinguishing Media: Dry Chemical Powder, Foam, CO ₂ and water or fog. Water may be used to					
cool below flash point.					
Unusual Fire or Explosion Hazards : Do not use forced stream as this could cause fire to spread.					
Combustion Products : Fumes, Smoke, and Carbon monoxide.					
Fire-fighting Instruction and Equipment : Use waste to cool containers exposed to flames.					
Do not enter enclosed or a confined work space without proper protective equipment.					
Fire fighting personnel should wear respiratory protection (positive pressure if					
available).					

Section 6 - Acci	dental release Measures		
	source if possible without risk. Contain spill.		
	area will be slick. Recover all possible material		
for reclamation. Use non-flammable absorbent material to pick up remainder of spill.			
	ial is spilled into navigable waters and creates		
a visible sheen, it is reportable to Local Response Centre.			
Section 7 - 1	Handling and Storage		
Handling and storage Precautions : Keep away from flames, sparks or hot surfaces. Never use			
a torch to cut or weld on or near container. Empty oil containers can contain explosive vapors. NFPA Class IIIB storage. Wash thoroughly after handling.			
	n soap and water before eating, drinking, smoking		
	nower after work if general contact occurs. Remove		
oil-soaked and launder before reuse. Discard contaminated shoes and leather gloves.			
Section 8 - Exposure	Controls/Personal Protection		
Engineering Controls: Adequate ventilation	on is required where excessive heating or agitation		
may occur to maintain concentration below exposures limits.			
Eye/Face Protection : Safety glasses or face shield where splashing is possible.			
Skin Protection : Avoid prolonged and or repeated skin contact. If prolonged contact can not			
be avoided, wear protective gloves (solvent resistant gloves) and			
clothing.	cettive groves (sorvent resistant groves) and		
_	wind Dessignators should be used in success where		
	uired. Respirator should be used in areas where		
	ion is excessive due to high temperatures or where		
oil misting occu	rs.		
	al and Chemical Properties		
Appearance : Clear, pale straw to yellow,	Vapor Pressure(mm Hg): 0.0059 mm Hg at 100°F		
Heavy liquid	Evaporation Rate : Not applicable		
Odor : Mild petroleum odor.	Solubility(H ₂ O): Negligible		
Specific Gravity: 0.81 to 0.89	PH : Not applicable		
(Water = 1)	Boiling Point :> 271°C		
% Volatiles by volume @21°C(70°F): Nil	Vapor Density(Air=1):> 5		
Melting Point: Not applicable			
Section 10 - Stability and reactivity			
Stability : Stable under ordinary conditions of use and storage.			
Polymerization : Polymerization will not	occur.		
Chemical Incompatibilities : Strong oxid			
Condition to Avoid : Source of ignition.			
Hazardous Decomposition Products : Combustion may produce carbon monoxide and carbon			
dioxide.			
Section 11 - Toxicological Information			
Eyes Effects: Minimal irritation on contact.			
Skin Effects : Practically non-toxic if absorbed. May cause mild irritation with prolonged			
and repeated exposure.			
Acute Oral Effects : Tests on similar material indicate low order of acute oral toxicity.			
Acute Inhalation Effects : Low acute toxicity expected on inhalation.			
Section 12 - Ecological Information			
Environmental Fate: No information found.			
	Environmental Toxicity: No information found.		
Environmental Toxicity: No information			

	Castion 19 Discuss 1 Considerations			
	Section 13 - Disposal Considerations			
	e and Local regulations. Not a RCRA hazardous waste if uncontaminated.			
	iteria must be determined. Do not flush to drain/storm sewer. If			
permitted incineratio	n may be practical. Consider recycling.			
	Section 14 - Transport Information			
DOT Shipping Label : N				
	Section 15 - Regulatory Information			
CERCLA/SARA :				
302/303/304 categorie	s : Extremely hazardous substances : None			
311/312 categories	: Immediate(acute) Health Effects : No			
	Delayed(chronic) health effects : No			
	Fire Hazards : No			
313 categories	: Toxic Chemicals(40 cFR 372) : None			
Clean Air act	: Hazardous Air Pollutants(HAPS) : None			
	Ozone depleting Compounds(ODC) : None			
	This product is not hazardous under Hazard Communication Standard			
	29 CFR 1910.1200			
EPA/TSCA Inventory	: The components of this product are listed on the EPA/TSCA inventory			
	of chemicals CAS No: 64742-53-6			
Foreign Inventories	: The components of this product are listed under the following			
inventories :				
1. CANADA DSL No.: 64742-53-6				
-	EINICS No. 265 – 156 – 6			
3. Korea's ECL No. KE – 12552				
4. Australia's ACS No. 64742 - 53 –6				
5. Philippine's PICCS - on list				
	Section 16 – Other Information			
	llation & Coolant media in Transformers.			
Hazard Rating NFPA/HMIS Classification				
0 = Least 1 = Slight 2 = Moderate Health = 1 3 = High 4 = Extreme Fire = 1				
ο = nign 4 = Extrem				
	Reactivity = 0			

Disclaimer :

The information contained herein is based upon data believed to be reliable and reflects our best professional judgment. It is the responsibility of the user to determine the suitability of the material for their purpose. No warranty is expressed or implied, is given \circ