

TOAP 1020 BSX

TOAP 1020 BS X is an Inhibited Transformer Oil meeting BS 148 Class I A& II A: 1984 Standard Specification.

It also meets the ASTM D 1275 B Test requirement for Corrosive Sulphur.

Sr No	Characteristics		Unit	Test Method	Guaranteed Data	
					Min	Max
1	Appearance			Representative sample of the oil shall be examined in transmitted light under an oil depth of 100 mm at ambient temperature	Clear free from sediment and suspended matter	
2	Density at 20°C		Kg/dm ³	BS 4714		0.895
3	Kinematic Viscosity at 40°C		mm ² /sec	BS 2000 Part 71		11
	at	20°C				25
		-15°C				800
		-30°C				1800
4	Flash Point, PMCC		°C	BS 2000 Part 34	140	
5	Pour Point		°C	BS 2000 Part 15		-45
6	Neutralization Value		mg KOH/gm	BS 2000 Part 1		0.08
7	Water Content, Bulk/Drum		ppm	BS 6470		30/40
8	Breakdown Voltage		kV	BS 5874		
	As Delivered				30	
9	Dielectric Dissipation Factor (Tanδ) 90°C & 40 to 62 Hz			BS 573		0.005
10	Corrosive Sulphur Copper Strip, 140°C, 19Hrs Copper Strip, 150°C, 48Hrs			BS 5680:1979 ASTM D 1275 B	Non Corrosive Non Corrosive	
11	Antioxidant Additives		%	BS 5984:1980	Not Requirement	
12	Oxidation Stability			BS 148: 1984 Appendix A		
	at 120°C, 164 Hrs	Total Acidity	mg KOH/gm			0.25
		Sludge	%			0.01
	at 120°C, 500 Hrs	Total Acidity	mg KOH/gm			1.5
Sludge		%		1.0		
13	Gassing Tendency at 50 Hz after 120 minutes		mm ³ /min	BS 5797 Method A		+8

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.