Section 1 - Chemical Product and Company Identification

Product Name: TRANSFORMER OIL TOAP 10X Chemical Family: Petroleum Distillate. Chemical Formula: Not Applicable

CAS Number: 64742-53-6

Company Details: TENOIT CO., LTD.

Room 4, 5FL., No. 109, Sec. 6, Mingquan East Road, Taipei, Taiwan

EMERGENCY TELEPHONE NUMBER: TEL (886) 2 8792–2185 8792–2187

FAX (886) 2 8792-2151

Section 2 - Composition And Information On Hazardous Ingredients

1		9	
Ingredient	CAS Number	Percentage	Hazardous
Severely Hydrotreated Light Naphthenic Petroleum Oil.	64742-53-6	99.6 to 99.85	No
Inhibitor	128-37-0	0.15 to 0.4	No

Section 3 - Hazardous Identification

Potential Health Effects Primary Entry Route: Skin

Inhalation: Inhalation of vapors or mist may be irritating to respiratory passages. Prolonged exposure may result in dizziness and nausea. Target Organ for mineral oil mist is lungs.

Eye: Eye contact may result in slight irritation and redness.

Skin: Short term contact with skin is unlikely to cause any problems; excessive or prolonged and repeated contact and poor hygiene conditions may result in dryness, dermatitis, oil acne, cracking and defatting of the skin. Personnel with pre-existing skin disorders should avoid contact with this product.

Ingestion: May result in nausea or stomach discomfort.

Section 4 - First Aid Measures

Eye Contact: Flush eyes immediately with plenty of water 15 minutes or until irritation. If redness persists, seek medical help.

Skin Contact: Wash thoroughly with soap and water. Remove contaminated clothing. Reuse only after clearing.

Inhalation: Remove to fresh air. Assist breathing if necessary. Seek medical help.
Aspiration: If there is any suspicion of aspiration into the lungs obtain medical advice.
Ingestion: If swallowed, observe for signs of stomach discomfort or nausea. If symptoms persist, seek medical help. Do induce vomiting.

Section 5 - Fire Fighting Measures

Flash Point: >140°C , Flash Point Method: COC

Auto ignition Temperature : $>315^{\circ}$ C

Lower Explosive Level(LEL): Not determined.
Upper Explosive Limit(UEL): Not determined.

Flammability Classification: OSHA CLASS III-B Combustible Liquid.

Extinguishing Media: Dry Chemical Powder, Foam, CO₂ and water or fog. Water may be used to cool below flash point.

Unusual Fire or Explosion Hazards: Do not use forced stream as this could cause fire to spread.

Combustion Products: Fumes, Smoke, and Carbon monoxide.

Fire-fighting Instruction and Equipment: Use waste to cool containers exposed to flames. Do not enter enclosed or a confined work space without proper protective equipment. Fire fighting personnel should wear respiratory protection (positive pressure if available).

Section 6 - Accidental release Measures

Spill/Leak Procedures: Stop spill at source if possible without risk. Contain spill. Eliminate sources of ignition Spill area will be slick. Recover all possible material for reclamation. Use non-flammable absorbent material to pick up remainder of spill.

Spill to navigable Waters: If this material is spilled into navigable waters and creates a visible sheen, it is reportable to Local Response Centre.

Section 7 - Handling and Storage

Handling and storage Precautions: Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty oil containers can contain explosive vapors. NFPA Class IIIB storage. Wash thoroughly after handling.

Work/Hygienic Practices: Wash hands with soap and water before eating, drinking, smoking or use of toilet facilities. Take shower after work if general contact occurs. Remove oil-soaked and launder before reuse. Discard contaminated shoes and leather gloves.

Section 8 - Exposure Controls/Personal Protection

Engineering Controls: Adequate ventilation is required where excessive heating or agitation may occur to maintain concentration below exposures limits.

Eye/Face Protection: Safety glasses or face shield where splashing is possible.

Skin Protection: Avoid prolonged and or repeated skin contact. If prolonged contact cannot be avoided, wear protective gloves (solvent resistant gloves) and clothing.

Respiratory Protection: Normally not required. Respirator should be used in areas where vapor concentration is excessive due to high temperatures or where oil misting occurs.

Section 9 - Physical and Chemical Properties

Appearance: Clear, pale straw to yellow,

Heavy liquid

Odor: Mild petroleum odor.

Specific Gravity: 0.81 to 0.89

(Water = 1)

% Volatiles by volume @21°C(70°F): Nil

Melting Point: Not applicable

Vapor Pressure(mm Hg): 0.0059 mm Hg at 100°F

Evaporation Rate: Not applicable Solubility(H2O): Negligible in water

PH: Not applicable Boiling Point:> 271℃

Vapor Density(Air=1):> 5

Section 10 - Stability and reactivity

Stability: Stable under ordinary conditions of use and storage.

Polymerization: Polymerization will not occur. **Chemical Incompatibilities:** Strong oxidizers.

Condition to Avoid: Source of ignition.

Hazardous Decomposition Products : Combustion may produce carbon monoxide and carbon dioxide \circ

Section 11 - Toxicological Information

Eve Effects: Minimal irritation on contact.

Skin Effects: Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.

Acute Oral Effects: Tests on similar material indicate low order of acute oral toxicity. Acute Inhalation Effects: Low acute toxicity expected on inhalation.

Section 12 - Ecological Information

Environmental Fate: No information found. Environmental Toxicity: No information found.

Section 13 - Disposal Considerations

Follow National, State and Local regulations. Not a RCRA hazardous waste if uncontaminated. If "used", RCRA criteria must be determined. Do not flush to drain/storm sewer. If permitted incineration may be practical. Consider recycling.

Section 14 - Transport Information

DOT Shipping Label: Not regulated by DOT

Section 15 - Regulatory Information

CERCLA/SARA:

302/303/304 categories : Extremely hazardous substances : None

311/312 categories : Immediate(acute) Health Effects : No

Delayed(chronic) health effects: No Fire Hazards: No : Toxic Chemicals(40 cFR 372): None

313 categories : Toxic Chemicals(40 cFR 372) : None Clean Air act : Hazardous Air Pollutants(HAPS) : None Ozone depleting Compounds(ODC) : None

OSHA(29CFR 1910) : This product is not hazardous under Hazard Communication Standard 29

CFR 1910.1200

EPA/TSCA Inventory: The components of this product are listed on the EPA/TSCA inventory

of chemicals CAS No: 64742-53-6

Foreign Inventories : The components of this product are listed under the following inventories :

1. CANADA DSL No.: 64742-53-6

- 2. European Union's EINICS No. 265 156 6
- 3. Korea's ECL No. KE 12552
- 4. Australia's ACS No. 64742 53 -6
- 5. Philippine's PICCS on list

Section 16 - Other Information

<u>Hazard Rating</u>			NFPA/HMIS Classification
$0 - I_{ooot}$	1 - Clight	2 - Modorato	$H_{00}1+h=1$

U = Least 1 = Slight 2 = Moderate Health = 1 3 = High 4 = Extreme Fire = 1 Reactivity = 0

Disclaimer:

The information contained herein is based upon data believed to be reliable and reflects our best professional judgment. It is the responsibility of the user to determine the suitability of the material for their purpose. No warranty is expressed or implied, is given.