

TOAP 10X

TOAP 10 X is an inhibited Transformer Oil meeting IEC 296 ClassII A:1982 Standard Specification.

It also meets the ASTM D 1275B Test requirement for Corrosive Sulphur.

Sr No	Characteristics		Unit	Test Method	Guaranteed Data	
					Min	Max
1	Appearance			Representative sample of the oil shall be examined in transmitted light under a thickness of 10 cm at ambient temperature	Clear free from sediment and suspended matter	
2	Density at 20°C		Kg/dm ³	ISO 3675		0.895
3	Kinematic Viscosity		mm ² /sec	ISO 3104		11
	at	40°C				25
		20°C				1800
		-30°C				
4	Flash Point, PMCC		°C	ISO 2719	130	
5	Pour Point		°C	ISO 3016		-45
6	Inter Facial Tension at 25°C		N/m	ISO 6275	0.04	
7	Neutralization Value		mg KOH/gm	7.7 of IEC 296		0.03
8	Water Content, Bulk/Drum		ppm	IEC 733		30/40
9	Breakdown Voltage			IEC 156		
	AS Delivered/After Treatment		kV			30/50
10	Dielectric Dissipation Factor (Tanδ) 90°C & 40 to 60 Hz			IEC 247		0.005
11	Corrosive Sulphur			ISO 5662 ASTM D 1275 B	Non Corrosive	
	Copper Strip, 140°C, 19Hrs Copper Strip, 150°C, 48Hrs				Non Corrosive	
12	Anti Oxidant Additives		%	IEC666 (Limits given as guideline only)	0.15	0.40
13	Oxidation Stability at 100°C, 164 Hrs			IEC 74		
	Induction Period		Hours	(Limits given as guideline only)	120	

Disclaimer: It makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.